LED

2200K, 2700K, 3000K, 4000K CRI>70, CRI>80 optional initial MacAdam 4 SDCM 80.000h L80

OPTIC

symmetric asymmetric

ELECTRIC

ON-OFF switchable DALI dim automatic DIM profile





DALI











Description

Top-mounted luminaire in elegant design. Versatile solution for professional illumination of side streets, traffic routes, residential areas, promenades and pedestrian zones. Aluminium housing in black powder-coated. Highly efficient LED technology with innovative lens system for optimal light intensity distribution. FULL CUT OFF system. Extremely weather-resistant and durable. Quick and easy mounting with stainless steel clamping screws. Additional adapters for wall and pole mounting available on request.



Types


PRODUCT CODE	POWER	LUMINOUS FLUX	COLOUR TEMP.	MOUNTING HIGH	WEIGHT
SDSA020.XXX13	20W	2.600lm	2200K 2700K 3000K 4000K	3-6m	7,4kg
SDSA040.XXX13	40W	5.100lm			7,6kg
SDSA060.XXX13	60W	7.600lm			7,9kg




1	Control
1.	ON-OFF switchable
2.	DALI dim
6	Automatic DIM Profi











STREET1203



Dimension





Automatic DIM profile



A customised, autonomous dimming profile with time intervals and light levels is programmed into the LED control gear. No additional wiring is required on the luminaire.

Full cut-off luminaire



Luminaires that are shielded upwards and do not emit light in and above the horizontal.

lasts and accessorie

All steel and aluminium masts incl. accessories are also available from UEBEX.